

ESPECIFICACIONES TUBERÍA PRESIÓN CON CAMPANA

		PRESIÓN DE TRABAJO DE AGUA										
		RDE	9	11	13,5	21	26	32,5	41	51	64	
		psi	500	400	315	200	160	125	100	80	63	
		MPa	3,50	2,80	2,17	1,38	1,10	0,86	0,69	0,56	0,43	
	Tamaño nominal (pulgadas)	Diámetro exterior nominal (mm)	Diámetro exterior promedio (mm)	ESPESOR MÍNIMO DE PARED (mm)								
				6,70	5,48	4,47	2,87	2,31	1,85	1,52	---	---
EXTREMO CON CAMPANA	2"	60	60,32	6,70	5,48	4,47	2,87	2,31	1,85	1,52	---	---
	2 1/2"	73	73,02	8,11	6,64	5,41	3,48	2,79	2,24	1,78	---	---
	3"	88	88,90	9,88	8,08	6,58	4,24	3,43	2,74	2,16	1,75	---
	4"	114	114,30	12,70	10,39	8,46	5,44	4,39	3,51	2,79	2,24	1,78
	6"	168	168,28	18,70	15,30	12,47	8,03	6,48	5,18	4,11	3,30	2,64

Productos certificados bajo la NTC 382 y la NTC 2295



PLANTA DE PRODUCCIÓN

Autopista Medellín, Kilómetro 7 Costado Norte (Sector Siberia) Tenjo - Cundinamarca - Colombia
 Tels: (57) (1) 877 2450 / 55 al 59 • Fax: (57) (1) 877 2460 • Cel: (57) 314 413 6780
 e-mails: morgan@productosmorgan.com.co • morgan8772450@gmail.com
 Bogotá - Colombia